

TEST REPORT

100 Clemson Research Blvd. Anderson, SC 29625 (864) 656-1094 Fax: (864) 656-1095



Results of Tests on brick Conducted in accordance with C67/C67M - 24 Standard Test Methods for Sampling and Testing Brick and Structural Clay Tile

07/24/2025

Plant:

Sampled Date:

Received Date:

Fired Date:

Sugarcreek

7/11/2025

7/11/2025

7/11/2025

The Belden Brick Company Name:

P. O. Box 430

Sugarcreek, OH 44681

Phone: 330-456-0031 Fax:

330-456-2694

14065-34934 Report Number:

> Description: PLT 2, Shale/Fireclay w/Additive Fine Grind (Face)

Absorption		1	2	3	4	5	Average	Test Date									
24 Hour Cold Water (%) 5 Hour Boiling Water (%) Saturation Coefficient		2.4 2.6 0.93	2.7 2.9 0.94	2.4 2.5 0.98	2.4 2.6 0.94	2.6 2.8 0.91	2.5 2.7 0.94	7/17/2025									
									Compressive Strength		1	2	3	4	5	Average	Test Date
										psi	15,860	20,100	17,470	19,390	19,700	18,500	7/21/2025
IRA (Oven Dried Method)		6	7	8	9	10	Average	Test Date									
g/min/3	30 in. ²	3.3	3.0	3.4	3.3	4.0	3.4	7/15/2025									
Efflorescence		11	12	13	14	15		Test Date									
Efflorescence Detection		Not	Not	Not	Not	Not		7/23/2025									
		Effloresced	Effloresced	Effloresced	Effloresced	Effloresced											
Void Area		1	2	3	4	5	Average	Test Date									
	Area (%)	21	21	21	21	21	21	7/15/2025									

The brick represented by the test results shown here comply with the physical property requirements of the standards listed below:

ASTM C216 - 24 Standard Specification for Facing Brick (Solid Masonry Units Made From Clay or Shale)

Grade: SW, MW

*The temperature and humidity of the Bishop Materials Laboratory is constantly kept between 60 -90F, and 30-70% RH. The sampling for these tests was done by the customer. These results are specific to the samples tested. A Simple Acceptance Decision Rule was applied when determining the conformity statement shown on this report. Reporting of test results follows the requirements of the appropriate ASTM Test Method. For information on the decision rules or measurement uncertainty, please contact Kathy Hill, BML Quality Manager. This test report shall not be reproduced except in full, without written approval of the laboratory.

Lab Reference: 14065.34934 Page 1 of 1